

isdtd

A8 Air

智能充电器操作说明书

WWW.ISDTCO

深圳艾斯特创新科技有限公司




230427Q

感谢您购买ISDT A8 Air 充电器
为确保安全和良好的用户体验,在使用本产品之前,请阅读这些说明和警告。
1.请勿使用非充电电池,及表面绝缘层已破损的电池;
2.使用过程中确保充电器远离热源及潮湿环境,并注意通风散热;
3.切勿让儿童玩耍电池及充电器。

产品规格

型号: A8 Air
输入: DC 5~9V
最大输出功率: 27W
最大充电电流: 1.00A/槽
电池尺寸: AAA, AA, 10500, 12500
电池类型: NiMH, NiCd, NiZn, Li-Ion, LiFePO4, LiHv, 1.5V恒压锂电
工作温度: -10℃ ~ 40℃
尺寸: 118.5 × 63 × 25毫米
重量: 75克

操作指引



1. USB Type-C 电源输入及电脑连接端口
2. AA电池负极触片
3. AAA电池负极触片
4. 电池正极触片
5. Led指示灯

A8 Air 最多可为任意组合的 8 颗AA或AAA电池充电

1. 确保电池的正极和负极与充电器的正极和负极匹配;
2. 将本产品USB Type-C接口与5-9V直流电源(手机适配器或电脑USB均可)连接,给电池充电;

LED指示灯说明

正常充电	对应通道指示灯快闪 (每1.5秒闪烁两次)
待机	全部指示灯缓慢闪烁 (每5秒闪烁一次)
升级	全部指示灯依次闪烁
充满	对应通道指示灯常亮
充电异常	对应通道指示灯快速闪烁 (每100毫秒闪烁一次)



下载并安装ISD Link App

1. 官网下载: 移动设备登录官方网站 www.isdtd.co, 在“技术支持-应用”软件下载“界面下载并安装;
2. 扫码下载: 移动设备直接扫描尾页对应二维码, 根据提示下载并安装。
3. 通过点击App右上角的“+” 根据提示添加设备即可开始使用。

*本产品所有图片、声明及文字资料仅供参考,

实际信息请参考官方网站 www.isdtd.co 。

深圳艾斯特创新科技有限公司拥有对本说明书内容的最终解释权 and 修改权。

isdtd

A8 Air

Smart Charger Operating Instructions

WWW.ISDTCO

Shenzhen ISD Technology CO.,LTD



230427Q


Thank you for purchasing ISDT A8 Air Smart USB battery charger.

- For your safety and a better user experience please read this manual and follow the instructions before using your new charger.
- 1, Never attempt to charge a broken surface of insulation or a non-rechargeable battery.
 - 2, Keep the charger away from humidity and high temperature
 - 3, Do not let children play with any batteries or chargers.

Specification

SMART CHARGER: A8 Air
Input Voltage and Current: DC 5~9V
Max Charging Power: 27W
Max Charging Current: 1.00A/slot
Battery Sizes: AAA, AA, 10500, 12500
Battery Types: NiMH, NiCd, NiZn, Li-Ion, LiFePO4, LiHv, 1.5V Lithium Rechargeable Battery
Operating Temperature: -10℃ - 40℃
Dimensions (LxWxH): 118.5 × 63 × 25mm
Weight: 75g

Operation Introduction



1. USB Type-C port for power input and PC connection port
2. AA battery negative plate
3. AAA battery negative plate
4. Battery positive plate
5. Status indicator LEDs

The A8 Air Smart USB Charger can charge 1-8 AA or AAA rechargeable batteries in any combination.

- When inserting batteries in to the charger always observe the correct polarity as marked on each battery slot.
- Connect the A8 Air battery charger to a 5-9V DC power source (such as a mobile phone USB power adapter or PC USB port) via its USB Type-C port.

LED Indicator Light Introduction

Normal charging	The corresponding channel indicator flashes quickly (twice every 1.5 seconds)
Standby	All indicator lights flash slowly (once every 5 seconds)
Upgrade	All indicator lights flash in sequence
Full charged	The corresponding channel indicator light is always on.
Abnormal charge	The corresponding channel indicator light flashes quickly (once every 100 milliseconds).



Download and Install App

1. Download from the official website: Log in to the official website www.isdtd.co with your mobile devices, download and install in the “Support- Software” interface;
2. Download by scanning code: You could use your mobile device directly scans the QR code corresponding to the last page, then downloads and installs it according to the prompts.
3. Click “+” on the upper right corner of App surface, then follow the direction to add the device to get started.

*All product photos, statements and literature are for reference only
For up-to-date information, please visit our official web www.isdtd.co
SHENZHEN ISD TECHNOLOGY CO., LTD.
ISDT reserves the right of final explanation and revision for the terms.

成品尺寸: 60*76 单色印刷 材质: 铜版纸80克 印刷颜色: C0 M0 Y0 K70